D¢LLTechnologies

OPTIPLEX 5090 TOWER, SMALL FORM FACTOR AND MICRO

Intelligent, mainstream desktops with right-sized performance & configurations.





IMPRESSIVELY POWERFUL

Built with up to 11th generation Intel[®] up to Core[™] i7 processors and doubled max memory from previous generation provides better performance while running multiple or large applications. The 5090 tower is ready to deliver entry commercial VR content experiences with the latest NVIDIA[™] 1660 Super and AMD[®] graphics.



FASTER USER EXPERIENCES

Select your top five apps and Dell Optimizer ExpressResponse will analyze and boost their performance. New ExpressConnect automatically joins the strongest access point and directs bandwidth to critical applications. Experience speedier multitasking, powerful data analytics and strong connectivity with integrated Intel® Wi-Fi 6 (WiFi 802.11ax).



SEE AND DO MORE

Drive up to a triple display set up with new Intel® Gen 12 graphics. Achieve better visuals for 3D rendering and 4K monitor use with discrete graphics support for 5090 micro. Connect with ease with two native DisplayPort interfaces with optional VGA, HDMI 2.0b, or USB Type-C® Alt mode.



SMART DESIGN

Sustainably built with a high ratio of post consumer recyclable (PCR) content and a design to keep your system cool, OptiPlex 5090 is a smart solution. Custom mounts and stands adapt to your workspace while the tool-less chassis provides easy serviceability. Protect your IT investment with TPM 2.0, optional chassis intrusion switch and lockable cable covers. EPEAT Gold and ENERGY STAR qualified on select configurations.

Recommended Accessories

OPTIPLEX 5090 TOWER. SMALL FORM FACTOR AND MICRO

CUSTOM STANDS AND MOUNTS



OPTIPLEX MICRO ALL-IN-ONE STAND

Small footprint mounting solution adapts to your environment, with cable management and monitor height adjustability, tilt, swivel and pivot functions.



OPTIPLEX MICRO ALL-IN-ONE MOUNT FOR DELL **E SERIES MONITORS**

This mount allows the Micro to be VESA mounted to select Dell E Series displays.



OPTIPLEX MICRO DUAL VESA MOUNT WITH ADAPTER BRACKET

Mount your system between two VESA compatible devices. Includes an adapter box to securely house the system's power adapter.



OPTIPLEX MICRO DVD+/-RW ENCLOSURE

Mount your system on a wall or under a surface with a VESA-compatible DVD+/-RW encolusure with full optical drive access. Includes an adapter box to securely house the system's power adapter.



OPTIPI EX MICRO VESA MOUNT WITH ADAPTER BRACKET

Mount your system on a wall or under a desk Includes an adapter box to securely house the system's power adapter.



DELL SINGLE MONITOR ARM | MSA20

Minimize your footprint with this arm that offers easy installation and enhanced adjustability while keeping cables neatly hidden from view.



OPTIPLEX SMALL FORM FACTOR ALL-IN-ONE STAND

Small footprint mounting solution featuring integrated monitor power and Ethernet cables, as well as monitor adjustability with height, tilt, swivel and pivot functions.

PURPOSE-BUILT SOLUTIONS



DELL 24 MONITOR | P2421D

Optimize your workspace with this efficient 23.8" monitor built with an ultrathin bezel, a small footprint and comfort-enhancing features.



DELL ULTRASHARP 24 MONITOR | U2422H

Take your work to new heights with this 23.8-inch FHD monitor with a wide color coverage. Features ComfortView Plus an always-on built-in low blue light screen, fast connectivity and transfer speeds.



DELL PROFESSIONAL SOUND BAR | AE515M

Optimize conference calls and multimedia Enhance your everyday productivity with streaming with exceptional audio clarity. Minimize background noise while on calls with the dual mic array and echo cancellation feature.



DELL PRO WIRELESS KEYBOARD AND MOUSE | KM5221W

a quiet full size keyboard and mouse combo that offers programmable shortcuts and 36 months battery life.



DELL WIRED MOUSE WITH FINGERPRINT READER I MS819

Wired mouse with fingerprint reader offers convenient and secure login and online access without passwords.



OPTIPLEX CABLE COVERS

Thermally tested custom cable covers offer an easy to install and attractive way to manage cables and secure ports.



OPTIPLEX DUST FILTERS

Custom dust filters safeguard internal components in factory, warehouse, or retail environments.



DELL PRO WIRED HEADSET | WH3022

Experience exceptional audio clarity with this Teams certified wired headset that allows you to wear the microphone on either side for a customized fit.

Workforce Modernization

It's more than a concept; it's our approach to modernizing your workforce. Our products, solutions and services support your IT team and help your employees work from home, the office, or a combination of both — simplifying and streamlining their work-life even if they're always on the move.

Dell Software & Services Solutions

END USER DEVICES

Provide the right device with the right software for any setting to give employees satisfaction and business perspective.

DEPLOY

Quickly get employees to work and save valuable IT time by provisioning applications at the factory and shipping ready-to-use devices directly to employees wherever they work.

SUPPORT

Automatically detect and proactively prevent issues through predictive analytics. Use our Al-driven insights to resolve issues remotely or leave time-consuming support issues in our hands with 24x7 access to our hardware and software experts.

MANAGE

Take advantage of the console of your choice to set up, configure, monitor and update your entire endpoint fleet.

Securely deliver and manage applications from the cloud, giving users smooth access to any device, including from other vendors.



Optimized experiences

Enhanced efficiency



SECURE

Use intelligent solutions that secure endpoints from both above and below the OS. Prevent, detect and remediate attacks. Detect outside attacks that have altered the BIOS. Encrypt sensitive data on devices and in the cloud. Protect credentials with built-in hardware.



aaS

You can enjoy modernization through different consumption models: Traditional cash purchase outright or as fixed monthly plan with no upfront investment.

OPTIPLEX 5090 TOWER, SMALL FORM FACTOR AND MICRO

Feature OptiPlex 5090 Technical Specifications¹

Processors1

Tower, Small Form Factor:

10th Generation Intel® Core™ i5-10400, 12MB Cache, 6 Core, 12 Treads, 2.9GHz to 4.3GHz, 65W 10th Generation Intel® Core™ i5-10500, 12MB Cache, 6 Core, 12 Treads, 3.1GHz to 4.5GHz, 65W 10th Generation Intel® Core™ i5-10600, 12MB Cache, 6 Core, 12 Treads, 3.3GHz to 4.8GHz, 65W 10th Generation Intel® Core™ i7-10700, 16MB Cache, 8 Core, 16 Treads, 2.9GHz to 4.8GHz, 65W 10th Generation Intel® Pentium™ Gold G6405, 4 MB Cache, 2 Core, 4 Threads, Up to 4.1 GHz, 58 W 10th Generation Intel® Pentium™ Gold G6505, 4 MB Cache, 2 Core, 4 Threads, Up to 4.2 GHz, 58 W 10th Generation Intel® Core™ i3-10105, 6 MB Cache, 4 Core, 8 Threads, 3.7 GHz to 4.4 GHz, 65 W 10th Generation Intel® Core™ i3-10305, 8 MB Cache, 4 Core, 8 Threads, 3.8 GHz to 4.5 GHz, 65 W 11th Generation Intel® Core™ i5-10505, 12 MB Cache, 6 Core, 12 Threads, 3.2 GHz to 4.6 GHz, 65 W 11th Generation Intel® Core™ i5-11500, 12 MB Cache, 6 Core, 12 Threads, 2.6 GHz to 4.6 GHz, 65 W 11th Generation Intel® Core™ i5-11600, 12 MB Cache, 6 Core, 12 Threads, 2.7 GHz to 4.8 GHz, 65 W 11th Generation Intel® Core™ i5-11600, 12 MB Cache, 6 Core, 12 Threads, 2.8 GHz to 4.8 GHz, 65 W 11th Generation Intel® Core™ i5-11600, 12 MB Cache, 6 Core, 12 Threads, 2.8 GHz to 4.8 GHz, 65 W 11th Generation Intel® Core™ i5-11600, 12 MB Cache, 6 Core, 12 Threads, 2.8 GHz to 4.9 GHz, 65 W 11th Generation Intel® Core™ i7-11700, 16 MB Cache, 8 Core, 16 Threads, 2.5 GHz to 4.9 GHz, 65 W

Micro:

10th Generation Intel® Core™ i5-10400T, 12MB Cache, 6 Core, 12 Treads, 2.0GHz to 3.6GHz, 35W 10th Generation Intel® Core™ i5-10500T, 12MB Cache, 6 Core, 12 Treads, 2.3GHz to 3.8GHz, 35W 10th Generation Intel® Core™ i5-10600T, 12MB Cache, 6 Core, 12 Treads, 2.4GHz to 4.0GHz, 35W 10th Generation Intel® Core™ i7-10700T, 16MB Cache, 8 Core, 16 Treads, 2.0GHz to 4.5GHz, 35W 10th Generation Intel® Core™ i3-10105T, 6 MB Cache, 4 Core, 8 Threads, 3 GHz to 3.9 GHz, 35 W 10th Generation Intel® Core™ i3-10305T, 8 MB Cache, 4 Core, 8 Threads, 3 GHz to 4 GHz, 35 W 10th Generation Intel® Pentium G6405T, 4 MB Cache, 2 Core, 4 Threads, 3.5 GHz, 35 W 10th Generation Intel® Pentium G6505T, 4 MB Cache, 2 Core, 4 Threads, 3.6 GHz, 35 W 11th Generation Intel® Core™ i5-11400T, 12 MB Cache, 6 Core, 12 Threads, 1.3 GHz to 3.7 GHz, 35 W 11th Generation Intel® Core™ i5-11500T, 12 MB Cache, 6 Core, 12 Threads, 1.5 GHz to 3.9 GHz, 35 W 11th Generation Intel® Core™ i5-11600T, 12 MB Cache, 6 Core, 12 Threads, 1.5 GHz to 4.1 GHz, 35 W 11th Generation Intel® Core™ i5-11600T, 12 MB Cache, 6 Core, 12 Threads, 1.7 GHz to 4.1 GHz, 35 W 11th Generation Intel® Core™ i5-11600T, 12 MB Cache, 8 Core, 16 Threads, 1.7 GHz to 4.1 GHz, 35 W 11th Generation Intel® Core™ i7-11700T, 16 MB Cache, 8 Core, 16 Threads, 1.4 GHz to 4.6 GHz, 35 W

Chipset

Intel® Q570 Chipset

Operating System Options¹

Windows 10 Home, 64-bit

Windows 10 IoT Enterprise 2019 LTSC (OEM only)

Windows 10 Pro, 64-bit

Windows 10 Pro Education, 64-bt

Kylin Linux Desktop version 10.1 (China only)

Ubuntu® Linux® 20.04 LTS, 64-bit

Windows 10 CMIT Government Edition 64-bit (China only)

Video Card^{2,14}

Tower.

Intel® UHD Graphics 610 for 10th Generation Intel® Pentium® Gold G6405 processors

Intel® UHD Graphics 630 for 10th Generation Intel® Pentium® Gold G6505 and 10th Generation Intel® Core™ i3/i5/i7 processors

Intel® UHD Graphics 730 for 11th Generation Intel® Core™ i5-11400 processors Intel® UHD Graphics 750 for 11th Generation Intel® Core™ i5/i7 processors

NVIDIA® GeForce® GTX 1660 Super™, 6 GB, GDDR6 (optional)

AMD Radeon™ RX640, 4 GB, GDDR5 (optional)
AMD Radeon™ 550, 2GB, GDDR5 (optional)

AMD Radeon™ 540, 1GB, GDDR5 (optional)

Small Form Factor:

Intel® UHD Graphics 610 for 10th Generation Intel Pentium G6405 processor

Intel® UHD Graphics 630 for 10th Generation Intel Pentium G6505 and Intel Core i3/i5/i7 processors

Intel® UHD Graphics 730 for 11th Generation Intel Core i5-11400 processor Intel® UHD Graphics 750 for 11th Generation Intel Core i5/i7 processors

AMD Radeon™ RX640, 4 GB, GDDR5 (optional) AMD Radeon™ 550, 2GB, GDDR5 (optional) AMD Radeon™ 540, 1GB, GDDR5 (optional)

Micro

Intel® UHD Graphics 610 for 10th Generation Intel® Pentium® Gold G6405T processors

Intel® UHD Graphics 630 for 10th Generation Intel® Pentium® Gold G6505T and 10th Generation Intel® Core™ i3/i5/i7 processors

Intel® UHD Graphics 730 for 11th Generation Intel® CoreTM i5-11400T processors Intel® UHD Graphics 750 for 11th Generation Intel® CoreTM i5/i7 processors

Memory^{2,3}

Tower:

4 GB, 1×4 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

8 GB, 1 x 8 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

8~GB, 2~x~4~GB, DDR4, 2666~MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933~MHz for 10^{th} Generation Intel Core i7,

3200 MHz for 11th Generation Intel Core i5/i7 processors

OPTIPLEX 5090 TOWER, SMALL FORM FACTOR AND MICRO

Feature

OptiPlex 5090 Technical Specifications¹

Memory^{1,2,3}

Tower

16 GB, 1×16 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

16 GB, 2 \times 8 GB, DDR4, 2666 MHz for Intel Pentium and 10th Generation Intel Core i3/i5, 2933 MHz for 10th Generation Intel Core i7, 3200 MHz for 11th Generation Intel Core i5/i7 processors

16 GB, 4 x 4 GB, DDR4, 2666 MHz for Intel Pentium and 10th Generation Intel Core i3/i5, 2933 MHz for 10th Generation Intel Core i7,

3200 MHz for 11^{th} Generation Intel Core i5/i7 processors 32 GB, 1×32 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7,

3200 MHz for 11^{th} Generation Intel Core i5/i7 processors 32 GB, 2 x 16 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7,

3200 MHz for 11^{th} Generation Intel Core i5/i7 processors 32 GB, 4 x 8 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

64 GB, 2 x 32 GB, DDR4, 2666 MHz for Intel Pentium and 10th Generation Intel Core i3/i5, 2933 MHz for 10th Generation Intel Core i7, 3200 MHz for 11th Generation Intel Core i5/i7 processors

64 GB, 4×16 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

128 GB, 4×32 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7 and 11^{th} Generation Intel Core i5/i7 processors

Note: The Memory speed varies by different type of DPC (DIMM per Channel) installation.

Small Form Factor:

4 GB, 1×4 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

8 GB, 1 x 8 GB, DDR4, 2666 MHz for Intel Pentium and 10th Generation Intel Core i3/i5, 2933 MHz for 10th Generation Intel Core i7, 3200 MHz for 11th Generation Intel Core i5/i7 processors

8 GB, 2×4 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

16 GB, 1 x 16 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

16 GB, 2 \times 8 GB, DDR4, 2666 MHz for Intel Pentium and 10th Generation Intel Core i3/i5, 2933 MHz for 10th Generation Intel Core i7, 3200 MHz for 11th Generation Intel Core i5/i7 processors

16 GB, 4 x 4 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i5/i7 processors

32 GB, 1×32 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

32 GB, 2×16 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

32 GB, 4 x 8 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

64 GB, 2×32 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i5, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

64 GB, 4×16 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

128 GB, 4 x 32 GB, DDR4, 2666 MHz for Intel Pentium and 10th Generation Intel Core i3/i5, 2933 MHz for 10th Generation Intel Core i7 and 11th Generation Intel Core i5/i7 processors

Micro

4 GB, 1×4 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

8 GB, 1×8 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

8 GB, 2 x 4 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

16 GB, 1 x 16 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

16 GB, 2 \times 8 GB, DDR4, 2666 MHz for Intel Pentium and 10th Generation Intel Core i3/i5, 2933 MHz for 10th Generation Intel Core i7, 3200 MHz for 11th Generation Intel Core i5/i7 processors

32 GB, 1×32 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

32 GB, 2×16 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i7, 3200 MHz for 11^{th} Generation Intel Core i5/i7 processors

64 GB, 2×32 GB, DDR4, 2666 MHz for Intel Pentium and 10^{th} Generation Intel Core i3/i5, 2933 MHz for 10^{th} Generation Intel Core i5/i7 processors

Wireless^{1,4}

Intel® AX201, 2x2 MIMO, 2.40 Gbps, 2.40 Ghz/5 GHz, Wi-Fi 6 (WiFi 802.11ax), Bluetooth 5.1 Qualcomm QCA9377, 1x1, 433 Mbps, 2.40/5 GHz, Wi-Fi 5 (WiFi 802.11ac), Bluetooth 5.0 Qualcomm QCA61x4A, 2x2, MIMO, 867 Mbps, 2.40 Ghz/5 GHz, Wi-Fi 5 (WiFi 802.11ac), Bluetooth 5.0

OPTIPLEX 5090 TOWER, SMALL FORM FACTOR AND MICRO

Feature OptiPlex 5090 Technical Specifications¹

Ports¹⁶ Tower:

Front:

2 USB 2.0 ports

1 USB 3.2 Gen 1 Type-A port 1 USB 3.2 Gen 2 Type-C® port

1 Universal Audio Jack

Rear:

2 USB 2.0 ports with Smart Power On

4 USB 3.2 Gen 1 Type-A port

1 RJ45 Ethernet port

1 re-tasking Line out/Line in audio port

2 DisplayPort 1.4 ports

1 VGA Port/DisplayPort 1.4 Port/HDMI 2.0b Port/ USB 3.2 Gen2 Type-C® Port with Alt-mode (optional)

1 Serial and 2 PS2 slot (optional)

Small Form Factor:

Front:

1 USB 3.2 Gen 1 Type-A port

1 USB 2.0 ports with PowerShare

1 USB 2.0 ports

1 USB 3.2 Gen 2 Type-C port

1 universal audio port

Rear:

4 USB 3.2 Gen 1 Type-A ports

2 USB 2.0 ports

1 re-tasking Line out/Line in audio port

2 DisplayPort 1.4 ports

1 RJ45 Ethernet port

Optional Modules:

1 VGA port

1 DisplayPort 1.4 port

1 HDMI 2.0b port

1 Serial/PS2 port

1 USB 3.2 Gen 2 type-C port with DisplayPort Alt Mode/Power delivery

Micro:

Front:

1 Universal Audio Jack

1 re-tasking Line-in/Line out audio port

1 USB 3.2 Gen 2x1 Type-C® port

1 USB 3.2 Gen 1 Type-A port with PowerShare

Rear:

1 RJ45 Ethernet port

1 Serial/Video port with Serial port/PS2 port/VGA port/DisplayPort 1.4 port/HDMI 2.0 Port/USB 3.2 Gen2 Type-C® Port with DP Alt-mode (optional)

1 USB 3.2 Gen 1 Type-A port

1 USB 3.2 Gen 1 Type-A port with Smart Power on

2 USB 3.2 Gen 1 Type-A ports

2 DisplayPort 1.4 ports

Optical Drive

Tower: 8x DVD-ROM, 8x DVD+/-RW; Small Form Factor: 8x DVD+/-RW (Optional); Micro: Dell OptiPlex Micro DVD/RW Enclosure Mount

Slots Tower

1 SD-card slot (optional)

1 full-height Gen 4 PCle x16 slot

1 full-height Gen 4 PCle x4 slot openend

2 full-height PCle x1 slots

1 M.2 2230 slot for Wi-Fi and Bluetooth card

1 M.2 2230/2280 slot for SSD

4 SATA slots for 2.5-inch HDD/SSD, and slim Optical Drive

Small Form Factor:

1 half-height Gen 3 PCle x16 slot

1 half-height Gen 3 PCle x4 slot

1 M.2 2230 slot for WiFi and Bluetooth card

1 M.2 2230/2280 slot for solid-state drive/Intel Optane

3 SATA 3.0 slots for 3.5/2.5-inch hard drive, slim optical drive

1 SD 4.0 card slot (optional)

Micro:

1 M.2 2230 slot for Wi-Fi and Bluetooth card 1 M.2 2230/2280 slot for SSD/Intel Optane

1 SATA slot for 2.5-inch hard drive

1 Kensington cable-lock slot

OPTIPLEX 5090 TOWER, SMALL FORM FACTOR AND MICRO

Feature OptiPlex 5090 Technical Specifications¹

Primary Hard Drive^{1,5}

Tower:

2.5-inch, 500 GB, 5400 RPM, SATA HDD 2.5-inch, 1 TB, 5400 RPM, SATA HDD 2.5-inch, 2 TB, 5400 RPM, SATA HDD 2.5-inch, 500 GB, 7200 RPM, SATA HDD 2.5-inch, 1 TB, 7200 RPM, SATA HDD

2.5-inch, 500 GB, 7200 RPM, SATA, HDD, Self-Encrypting, Opal 2.0, FIPS

3.5-inch, 500 GB, 7200 RPM, SATA, HDD 3.5-inch, 1 TB, 7200 RPM, SATA, HDD 3.5-inch, 2 TB, 7200 RPM, SATA, HDD 3.5-inch, 4 TB, 5400 RPM, SATA, HDD

M.2 2230, 128 GB, PCIe NVMe Gen3 x4, Class 35 SSD M.2 2230, 256 GB, PCIe NVMe Gen3 x4, Class 35 SSD

M.2 2230, 512 GB, PCle NVMe Gen3 x4, Class 35 SSD

M.2 2280, 256 GB, PCle NVMe Gen3 x4, Class 40 SSD M.2 2280, 512 GB, PCle NVMe Gen3 x4, Class 40 SSD

M.2 2280, 1 TB, PCIe NVMe Gen3 x4, Class 40 SSD M.2 2280, 2 TB, PCIe NVMe Gen4 x4, Class 40 SSD

M.2 2280, 256 GB, PCle NVMe Gen3 x4, Class 40 SSD, self-encrypting drive M.2 2280, 512 GB, PCle NVMe Gen3 x4, Class 40 SSD, self-encrypting drive

M.2 2280, 1 TB, PCle NVMe Gen3 x4, Class 40 SSD, self-encrypting drive

Small Form Factor:

 $2.5\text{-inch,}\ 500\ \text{GB,}\ 5400\ \text{RPM,}\ \text{SATA,}\ \text{HDD}$

2.5-inch, 1 TB, 5400 RPM, SATA, HDD

2.5-inch, 2 TB, 5400 RPM, SATA, HDD

2.5-inch, 500 GB, 7200 RPM, SATA, HDD

2.5-inch, 1 TB, 7200 RPM, SATA, HDD

2.5-inch, 500 GB, 7200 RPM, SATA, HDD, Self-Encrypting, Opal 2.0, FIPS

3.5-inch, 500 GB, 5400 RPM, SATA, HDD 3.5-inch, 1 TB, 7200 RPM, SATA, HDD 3.5-inch, 2 TB, 7200 RPM, SATA, HDD

3.5-inch, 4 TB, 7200 RPM, SATA, HDD

M.2 2230, 128 GB, PCle NVMe Gen3 x4, Class 35 SSD

M.2 2230, 256 GB, PCle NVMe Gen3 x4, Class 35 SSD

M.2 2230, 512 GB, PCle NVMe Gen3 x4, Class 35 SSD

 $\mathsf{M.2}$ 2280, 256 GB, PCIe NVMe Gen3 x4, Class 40 SSD

M.2 2280, 512 GB, PCle NVMe Gen3 x4, Class 40 SSD

 $M.2\ 2280, 1\,TB,$ PCIe NVMe Gen $3\ x4,$ Class $40\ SSD$

M.2 2280, 256 GB, PCle NVMe Gen3 x4, Class 40 SSD, self-encrypting drive M.2 2280, 512 GB, PCle NVMe Gen3 x4, Class 40 SSD, self-encrypting drive M.2 2280, 1TB, PCle NVMe Gen3 x4, Class 40 SSD, self-encrypting drive

Primary Hard Drive^{1,5}

Micro:

2.5-inch, 1 TB, 5400 RPM, SATA, HDD

2.5-inch, 2 TB, 5400 RPM, SATA, HDD

2.5-inch, 500 GB, 7200 RPM, SATA, HDD

2.5-inch, 1 TB, 7200 RPM, SATA, HDD

2.5-inch, 500 GB, 7200 RPM, SATA, HDD, Self-Encrypting, Opal 2.0, FIPS

2.5-inch, 500 GB, 5400 RPM, SATA, HDD

M.2 2230, 128 GB, PCle NVMe Gen3 x4, Class 35 SSD

M.2 2230, 256 GB, PCle NVMe Gen3 x4, Class 35 SSD

 $\mathsf{M.2}$ 2230, 512 GB, PCle NVMe Gen3 x4, Class 35 SSD

M.2 2280, 256 GB, PCle NVMe Gen3 x4, Class 40 SSD

M.2 2280, 512 GB, PCIe NVMe Gen3 x4, Class 40 SSD M.2 2280, 1 TB, PCIe NVMe Gen3 x4, Class 40 SSD

M.2 2280, 2 TB, PCle NVMe Gen4 x4, Class 40 SSD

M.2 2280, 256 GB, PCle NVMe Gen3 x4, Class 40 SSD, self-encrypting drive

M.2 2280, 512 GB, PCle NVMe Gen3 x4, Class 40 SSD, self-encrypting drive

M.2 2280, 1 TB, PCle NVMe Gen3 x4, Class 40 SSD, self-encrypting drive

Intel Optane Memory for Tower, Small Form Factor and Micro: Intel® Optane™ Memory H20 32 GB with 512 GB SSD

OPTIPLEX 5090 TOWER, SMALL FORM FACTOR AND MICRO

Feature

OptiPlex 5090 Technical Specifications¹

Dimensions

Tower:

US Dimensions

Front Height: 12.77 in. (324.30 mm) Rear Height: 12.77 in. (324.30 mm) Width 6.60 in. (154 mm) Depth 11.54 in. (293.00 mm) Weight (min): 11.07 lb (5.03 kg) Weight (max): 15.95 lb (7.24 kg)

ROW Dimensions

Front Height: 324.30 mm (12.77 in.) Rear Height: 324.30 mm (12.77 in.) Width: 154.00 mm (6.06 in.) Depth: 292.00 mm (11.5 in.) Weight (min): 5.90 kg (13.01 lb) Weight (max): 7.21 kg (15.90 lb)

India Dimensions

Front Height: 324.30 mm Rear Height: 292.00 mm Width: 154.00 mm Depth: 292.00 mm Weight (min): 5.90 kg Weight (max): 7.21 kg

Small Form Factor:

US Dimensions

Height: 11.42 in. (290.00 mm) Width 3.65 in. (92.6 mm) Depth 11.53 in. (292.80 mm) Weight (min): 9.77 lb (4.43 kg) Weight (max): 12.53 lb (5.66 kg)

ROW Dimensions

Height: 290 mm (11.42 in.) Width: 92.60 mm (3.65 in.) Depth: 292.80 mm (11.53 in.) Weight(minimum): 4.43 kg (9.76 lb) Weight(maximum): 5.65 kg (12.53 lb)

India Dimensions

Height: 290 mm Width: 92.60 mm Depth: 292.80 mm Weight(minimum): 4.43 kg Weight(maximum): 5.65 kg

Micro

US Dimensions

Height: 7.2 in. (183.00 mm) Width 1.4 in. (36.00 mm) Depth 7.0 in. (178.50 mm) Weight (min): 2.56 lb (1.16 kg) Weight (max): 2.83 lb (1.28 kg)

ROW Dimensions

Height: 182 mm (7.16 in.) Width: 178.50 mm (7.02 in.) Depth: 36 mm (1.41 in.) Weight: 1.17 kg (2.58 lb)

India Dimensions

Height: 182 mm Width: 178.50 mm Depth: 36 mm Weight: 1.17 kg

Power

Tower

260 W typical 85% Efficient PSU, 80 Plus Bronze 300 W typical 92% Efficient PSU, 80 Plus Platinum 360 W typical 92% Efficient PSU, 80 Plus Platinum

Small Form Factor:

300 W typical 92% Efficient PSU, 80 Plus Platinum 200 W typical 85% Efficient PSU, 80 Plus Bronze

Micro:

90 W AC adapter, 4.5 mm barrel for 35 W CPU (<=6C) 130 W AC adapter, 4.5 mm barrel for 35 W CPU (8C)

Hardware Security

1 Kensington security-cable slot

1 Padlock loop

Chassis lock slot support Chassis intrusion switch Lockable cable covers Supply chain tamper alerts

SafeID including Trusted Platform Module (TPM) 2.0

Smart card keyboard (FIPS)

Microsoft 10 Device Guard and Credential Guard (Enterprise SKU)

Microsoft Windows Bitlocker

Local hard drive data wipe through BIOS (Secure Erase)

Self-encrypting storage drives (Opal, FIPS)

Trusted Platform Module TPM 2.0

China TPM Intel Secure Boot

Intel Secure Boot Intel Authenticate

SafeBIOS: includes Dell Off-host BIOS Verification, BIOS Resilience, BIOS Recovery, and additional BIOS Controls

OPTIPLEX 5090 TOWER, SMALL FORM FACTOR AND MICRO

Feature OptiPlex 5090 Technical Specifications¹

Recommended accessories Monitors: Qualified with select Dell UltraSharp, Professional, and E-series monitors

Keyboards: Dell Premier Multi-Device Wireless Keyboard and Mouse, Dell wired keyboard with multimedia functionality, Dell

Smart Card keyboard, Dell wireless keyboard

Mouse: Dell wired mouse, Dell wireless mouse, Dell Laser mouse, Dell Wired Fingerprint Reader Mouse

Audio Speakers: Internal Dell Business audio speaker, Dell stereo speaker systems; Dell sound bar for select flat-panel

displays. Dell Wireless Speaker System **Audio Headsets**: Dell Pro Stereo headsets

Micro Mounting Options: Micro Vertical Stand, Micro VESA Mount, Micro Dual VESA Mount, Micro All-in-One Stand,

Micro All-in-One Mount for E Series Displays, Micro DVD+/-RW Enclosure Small Form Factor Mounting Option: Small Form Factor All-in-One Stand

Productivity Software Microsoft® Office 30 Day Trial, Microsoft® Office Home and Business 2019, Microsoft® Office Professional 2019

Audio and Speakers¹ Tower & Micro::

Stereo speakers with Waves MaxxAudio® Pro, 2 W x 2 = 4 W total

Small Form Factor:

Mono speaker with Waves MaxxAudio®, 2 W

Systems Management Options⁹ Dell Client Command Suite for In-Band systems management Intel® Standard Manageability

Regulatory^{9,10} ENERGY STAR qualified configurations available

EPEAT Registered configurations available TCO 8.0 certified configurations available

CEL WEEE

Japan Energy Law South Korea E-standby

EU RoHS China RoHS

Warranty 3 years hardware warranty with on-site service after remote diagnosis

4 years hardware warranty with on-site service after remote diagnosis 5 years hardware warranty with on-site service after remote diagnosis

3 years ProSupport with Next Business Day on-site service
4 years ProSupport with Next Business Day on-site service
5 years ProSupport with Next Business Day on-site service
3 years ProSupport Plus with Next Business Day on-site service
4 years ProSupport Plus with Next Business Day on-site service
5 years ProSupport Plus with Next Business Day on-site service

Accidental Damage Services 3 years Accidental Damage Service, 4 years Accidental Damage Service, 5 years Accidental Damage Service

Configuration Services Factory image load, BIOS customization, Hardware customization, Asset Tagging and Reporting



OPTIPLEX 5090 TOWER. SMALL FORM FACTOR AND MICRO

Intelligent, mainstream desktops with right-sized performance & configurations.



Discover professional class desktops at www.dell.com/OptiPlex

- 1. Offering may vary by region. Some items may be available after product introduction. For complete details, refer to the Technical Guidebook published on www.dell.com/support.
- 2. System Memory and Graphics: Significant system memory may be used to support graphics, depending on system memory size and other factors.
- 3. 4GB or Greater System Memory Capability: A 64-bit operating system is required to support 4GB or more of system memory.
- 4. Particular versions of Microsoft Windows may not support the full Bluetooth 4.2 functionality
- 5. Storage Option: GB means 1 billion bytes and TB equals 1 trillion bytes; actual capacity varies with preloaded material and operating environment and will be less.
- 6. TPM is available in selected regions.
- 7. Computrace: Not a Dell offer. Certain conditions apply. For full details, see terms and conditions at www.lojackforlaptops.com.
- 8. Please refer to www.epeat.net for specific country registration rating and participation.
- 9. Limited Hardware Warranty: For copy of Ltd Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see www.dell.com/warranty.
- 10. on-site service after Remote Diagnosis: Remote Diagnosis is determination by online/phone technician of cause of issue; may involve customer access to inside of system and multiple or extended sessions. If issue is covered by Limited Hardware Warranty (www.dell.com/warranty) and not resolved remotely, technician and/or part will be dispatched, usually within 1 business day following completion of Remote Diagnosis. Availability varies. Other conditions apply.
- 11. Dell Services: Availability and terms of Dell Services vary by region. For more information, visit www.dell.com/servicedescriptions.
- 12. For complete listing of declarations and certifications, refer to the Dell Regulatory and Environmental Datasheet found in the Manuals section of Product Support information www.dell.com/support/home/us/en/19.