



Dell PowerEdge RAID Controller H710P

An eight-port 6Gb/s PCI Express RAID controller, the Dell PowerEdge RAID Controller (PERC) H710P supports up to thirty-two 3Gb/s and 6Gb/s SATA or SAS hard-disk drives or solid-state drives.

As storage demands expand and processing loads grow, it becomes increasingly more difficult for administrators to achieve maximum performance from their applications. The newest line of Dell™ PowerEdge™ RAID Controller cards, built on the LSISA2208 dual-core PowerPC RAID-on-Chip (ROC), offer unmatched I/O performance for database applications and streaming digital media environments.

The PowerEdge RAID Controller (PERC) H710P, with eight internal ports, delivers two PowerPC processor cores and a 72-bit DDR3 interface that drives 1 GB cache memory. You can deploy the PERC H710P in hard-drive-based server environments for significant performance gains. If you are implementing hybrid server platforms based on solid-state storage, these next-generation PERCs exploit the potential of solid-state drives (SSDs) for unsurpassed performance and enterprise-class reliability.

Advanced software options

The Dell family of 6Gb/s PowerEdge RAID Controllers is designed to support advanced software options for the Dell PowerEdge server family with enhanced performance and data protection capabilities. These new software options can help you to address key business challenges while helping to deliver a higher return on your IT investments. The PERC CacheCade™ software and Dell's Cut Through I/O (CTIO) feature boost transactional I/O performance of both rotational hard-drive and SSD configurations.

Dell's FastPath™ software feature enables the use of the second core on our PowerPC chip to accelerate write-through I/O, which significantly enhances SSD performance.

Enterprise data protection

Standard support for the most popular RAID levels and accessories, including RAID 5, RAID 6, RAID 50, RAID 60 and NVCache, further strengthen the data-protection capabilities of the PERC H710P. Dell's NVCache technology backs up the data to non-volatile storage in a power-loss event, and can store it safely for a nearly unlimited period of time.

Intuitive RAID management utility

Dell OpenManage™ Storage Services (OMSS) provides the essential tools to efficiently manage PERC products, whether deployed in an enterprise or small business. Dell offers a collection of applications and tools, including a pre-boot setup utility and a full spectrum of online RAID management utilities. This suite of applications allow administrators to adjust SAS or SATA topology views from the system host, controller and disk enclosure down to the logical and physical drive level. Extending to enterprise deployments, these tools can scale to easily configure, monitor and manage RAID and JBOD volumes locally or over the LAN network.

The PERC H710P supports up to thirty-two 3Gb/s and 6Gb/s SATA or SAS hard-disk drives or solid-state drives.

Feature	PERC H710P technical specification																		
Solution provided	Eight-port internal SATA+SAS solution supporting up to 32 hard disk drives (HDDs) and solid-state drives (SSDs)																		
Physical dimensions	167.6mm (6.6in) x 64.4mm (2.5in) (MD2 low profile)																		
Connectors	Two internal mini-SAS SFF8088																		
Device support	Up to 32 (SAS, SATA)																		
Host bus type	8-lane, PCI Express 2.0 compliant																		
Data transfer rates	Up to 6Gb/s per port																		
SAS controller	LSISAS2208 dual-core PowerPC ROC																		
Cache size	1GB																		
Key RAID data protection features	<table border="0"> <tr> <td>RAID levels 0, 1, 5, 6</td> <td>Load balancing</td> </tr> <tr> <td>RAID spans 10, 50, 60</td> <td>Fast initialization for quick array setup</td> </tr> <tr> <td>Online Capacity Expansion (OCE)</td> <td>Configurable stripe size up to 1MB</td> </tr> <tr> <td>Online RAID Level Migration (RLM)</td> <td>SSD support</td> </tr> <tr> <td>Auto resume after power loss during array rebuild or reconstruction/RLM</td> <td>Patrol read for media scanning and repairing</td> </tr> <tr> <td>Consistency check for background data integrity</td> <td>Up to 64 logical drive and 64TB LUN support</td> </tr> <tr> <td>Physical disk power management (Dimmer Switch™)</td> <td>DDF compliant Configuration on Disk (COD)</td> </tr> <tr> <td>SED drive support</td> <td>S.M.A.R.T. support</td> </tr> <tr> <td></td> <td>Global and dedicated hot spare with revertible hot-spare support: automatic rebuild, enclosure affinity, emergency SATA</td> </tr> </table>	RAID levels 0, 1, 5, 6	Load balancing	RAID spans 10, 50, 60	Fast initialization for quick array setup	Online Capacity Expansion (OCE)	Configurable stripe size up to 1MB	Online RAID Level Migration (RLM)	SSD support	Auto resume after power loss during array rebuild or reconstruction/RLM	Patrol read for media scanning and repairing	Consistency check for background data integrity	Up to 64 logical drive and 64TB LUN support	Physical disk power management (Dimmer Switch™)	DDF compliant Configuration on Disk (COD)	SED drive support	S.M.A.R.T. support		Global and dedicated hot spare with revertible hot-spare support: automatic rebuild, enclosure affinity, emergency SATA
RAID levels 0, 1, 5, 6	Load balancing																		
RAID spans 10, 50, 60	Fast initialization for quick array setup																		
Online Capacity Expansion (OCE)	Configurable stripe size up to 1MB																		
Online RAID Level Migration (RLM)	SSD support																		
Auto resume after power loss during array rebuild or reconstruction/RLM	Patrol read for media scanning and repairing																		
Consistency check for background data integrity	Up to 64 logical drive and 64TB LUN support																		
Physical disk power management (Dimmer Switch™)	DDF compliant Configuration on Disk (COD)																		
SED drive support	S.M.A.R.T. support																		
	Global and dedicated hot spare with revertible hot-spare support: automatic rebuild, enclosure affinity, emergency SATA																		
RAID management	CTRL-R Dell OpenManage™ Storage Services Additional management: UEFI (HII) CEM																		
Operating temperature	Maximum ambient temperature: 60°C																		
Operating voltage	+3.3V																		
Optional SSD optimization	CacheCade™ software: provides boost in READs from SSD cache Dell FastPath™ software: delivers high IOPs performance on SSD arrays																		
Operating systems	Microsoft® Windows Server® 2008 R2 SP2 Red Hat® Enterprise Linux® 5.7 Red Hat® Enterprise Linux® 6.1 SUSE® Linux Enterprise Server 10 SP4 SUSE® Linux Enterprise Server 11 SP2 Virtualization options: VMware® ESX/ESXi 4.1 VMware® 5.0 UL																		
Warranty	Up to five-year warranty available for controller (up to the length of purchased system warranty) Three-year warranty for battery																		

Global services and support

Dell Services can help reduce IT complexity, lower costs and eliminate inefficiencies by making IT and business solutions work harder for you. The Dell Services team takes a holistic view of your needs, and designs solutions for your environment and business objectives while leveraging proven delivery methods, local talent and in-depth domain knowledge for the lowest total cost of ownership.

Learn more at Dell.com/PERC

© 2012 Dell Inc. All rights reserved. Dell, the DELL logo, the DELL badge, PowerEdge, and OpenManage are trademarks of Dell Inc. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind.

